

810 Invoice O/B from CCBCC

X12/V4010/810: 810 Invoice

Version: 1.0 Draft

Author:	CCBCC EDI-EAI Team
Publication:	March 15, 2007
Trading Partner:	Generic 4010
Modified:	02/13/2007
Notes:	Confidential

Table of Contents

810 Invoice	1
ST Transaction Set Header	2
BIG Beginning Segment for Invoice	3
REF Reference Identification	4
N1 Loop N1	5
N1 Name	6
N3 Address Information	7
N4 Geographic Location	8
DTM Date/Time Reference	9
IT1 Loop IT1	10
IT1 Baseline Item Data (Invoice)	11
PID Loop PID	13
PID Product/Item Description	14
TDS Total Monetary Value Summary	15
CTT Transaction Totals	16
SE Transaction Set Trailer	17

810 Invoice

Functional Group=IN

Purpose: This Draft Standard for Trial Use contains the format and establishes the data contents of the Invoice Transaction Set (810) for use within the context of an Electronic Data Interchange (EDI) environment. The transaction set can be used to provide for customary and established business and industry practice relative to the billing for goods and services provided.

Heading:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
010	ST	Transaction Set Header	M	1			Must use
020	BIG	Beginning Segment for Invoice	M	1			Must use
050	REF	Reference Identification	O	12			Must use
LOOP ID - N1					<u>200</u>		
070	N1	Name	O	1			Must use
090	N3	Address Information	O	2			Must use
100	N4	Geographic Location	O	1			Must use
140	DTM	Date/Time Reference	O	10			Must use

Detail:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
LOOP ID - IT1					<u>200000</u>		
010	IT1	Baseline Item Data (Invoice)	O	1			Must use
LOOP ID - PID					<u>1000</u>		
060	PID	Product/Item Description	O	1			Must use

Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
010	TDS	Total Monetary Value Summary	M	1			Must use
070	CTT	Transaction Totals	O	1		N3/070	Must use
080	SE	Transaction Set Trailer	M	1			Must use

Notes:

3/070 Number of line items (CTT01) is the accumulation of the number of IT1 segments. If used, hash total (CTT02) is the sum of the value of quantities invoiced (IT102) for each IT1 segment.

ST Transaction Set Header

Pos: 010	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

Purpose: To indicate the start of a transaction set and to assign a control number

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ST01	143	Transaction Set Identifier Code	M	ID	3/3	Must use

Description: Code uniquely identifying a Transaction Set

Code Name
810 Invoice

ST02	329	Transaction Set Control Number	M	AN	4/9	Must use
------	-----	---------------------------------------	---	----	-----	----------

Description: Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set

Semantics:

1. The transaction set identifier (ST01) used by the translation routines of the interchange partners to select the appropriate transaction set definition (e.g., 810 selects the Invoice Transaction Set).

CCBCC Example:

ST*810*135246~

BIG Beginning Segment for Invoice

Pos: 020	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 3

User Option (Usage): Must use

Purpose: To indicate the beginning of an invoice transaction set and transmit identifying numbers and dates

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
BIG01	373	Date	M	DT	8/8	Must use
		Description: Date expressed as CCYYMMDD				
BIG02	76	Invoice Number	M	AN	1/22	Must use
		Description: Identifying number assigned by issuer				
BIG07	640	Transaction Type Code	O	ID	2/2	Used
		Description: Code specifying the type of transaction				
		<u>Code</u> <u>Name</u>				
		CR Credit Memo				

Semantics:

1. BIG01 is the invoice issue date.
2. BIG03 is the date assigned by the purchaser to purchase order.
3. BIG10 indicates the consolidated invoice number. When BIG07 contains code CI, BIG10 is not used.

Comments:

1. BIG07 is used only to further define the type of invoice when needed.

CCBCC Example:

BIG*20070207*60123456070207~

REF Reference Identification

Pos: 050	Max: 12
Heading - Optional	
Loop: N/A	Elements: 2

User Option (Usage): Must use

Purpose: To specify identifying information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
REF01	128	Reference Identification Qualifier	M	ID	2/3	Must use

Description: Code qualifying the Reference Identification

Code Name

IA Internal Vendor Number

REF02	127	Reference Identification	X	AN	1/30	Must use
-------	-----	--------------------------	---	----	------	----------

Description: Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier

Syntax Rules:

1. R0203 - At least one of REF02 or REF03 is required.

Semantics:

1. REF04 contains data relating to the value cited in REF02.

CCBCC Example:

*REF*IA*1234~*

Loop N1

Pos: 070	Repeat: 200
Optional	
Loop: N1	Elements: N/A

User Option (Usage): Must use

Purpose: To identify a party by type of organization, name, and code

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
070	N1	Name	O	1		Must use
090	N3	Address Information	O	2		Must use
100	N4	Geographic Location	O	1		Must use

N1 Name

Pos: 070	Max: 1
Heading - Optional	
Loop: N1	Elements: 4

User Option (Usage): Must use

Purpose: To identify a party by type of organization, name, and code

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N101	98	Entity Identifier Code	M	ID	2/3	Must use
Description: Code identifying an organizational entity, a physical location, property or an individual						
Code Name						
RE Party to receive commercial invoice remittance						
ST Ship To						
N102	93	Name	X	AN	1/60	Must use
Description: Free-form name						
N103	66	Identification Code Qualifier	X	ID	1/2	Must use
Description: Code designating the system/method of code structure used for Identification Code (67)						
Code Name						
9 D-U-N-S+4, D-U-N-S Number with Four Character Suffix						
92 Assigned by Buyer or Buyer's Agent						
N104	67	Identification Code	X	AN	2/80	Must use
Description: Code identifying a party or other code						

Syntax Rules:

1. R0203 - At least one of N102 or N103 is required.
2. P0304 - If either N103 or N104 is present, then the other is required.

Comments:

1. This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the "ID Code" (N104) must provide a key to the table maintained by the transaction processing party.
2. N105 and N106 further define the type of entity in N101.

CCBCC Example:

N1*ST*CUSTOMER ABC #0010 V#1234*92*0010~

N3 Address Information

Pos: 090	Max: 2
Heading - Optional	
Loop: N1	Elements: 2

User Option (Usage): Must use

Purpose: To specify the location of the named party

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N301	166	Address Information	M	AN	1/55	Must use
		Description: Address information				
N302	166	Address Information	O	AN	1/55	Used
		Description: Address information				

CCBCC Example:

*N3*987 SPRITE HWY*PO BOX 100~*

N4 Geographic Location

Pos: 100	Max: 1
Heading - Optional	
Loop: N1	Elements: 3

User Option (Usage): Must use

Purpose: To specify the geographic place of the named party

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N401	19	City Name	O	AN	2/30	Must use
		Description: Free-form text for city name				
N402	156	State or Province Code	O	ID	2/2	Must use
		Description: Code (Standard State/Province) as defined by appropriate government agency				
N403	116	Postal Code	O	ID	3/15	Must use
		Description: Code defining international postal zone code excluding punctuation and blanks (zip code for United States)				

Syntax Rules:

1. C0605 - If N406 is present, then N405 is required.

Comments:

1. A combination of either N401 through N404, or N405 and N406 may be adequate to specify a location.
2. N402 is required only if city name (N401) is in the U.S. or Canada.

CCBCC Example:

*N4*DASANI*NC*234560100~*

DTM Date/Time Reference

Pos: 140	Max: 10
Heading - Optional	
Loop: N/A	Elements: 2

User Option (Usage): Must use

Purpose: To specify pertinent dates and times

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
DTM01	374	Date/Time Qualifier	M	ID	3/3	Must use
Description: Code specifying type of date or time, or both date and time						
Code Name						
011 Shipped						
DTM02	373	Date	X	DT	8/8	Must use
Description: Date expressed as CCYYMMDD						

Syntax Rules:

1. R020305 - At least one of DTM02, DTM03 or DTM05 is required.
2. C0403 - If DTM04 is present, then DTM03 is required.
3. P0506 - If either DTM05 or DTM06 is present, then the other is required.

CCBCC Example:

*DTM*011*20070207~*

Loop IT1

Pos: 010	Repeat: 200000
Optional	
Loop: IT1	Elements: N/A

User Option (Usage): Must use

Purpose: To specify the basic and most frequently used line item data for the invoice and related transactions

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
010	IT1	Baseline Item Data (Invoice)	O	1		Must use
060		Loop PID	O		1000	Must use

IT1 Baseline Item Data (Invoice)

Pos: 010	Max: 1
Detail - Optional	
Loop: IT1	Elements: 5

User Option (Usage): Must use

Purpose: To specify the basic and most frequently used line item data for the invoice and related transactions

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
IT102	358	Quantity Invoiced	X	R	1/10	Must use
		Description: Number of units invoiced (supplier units)				
IT103	355	Unit or Basis for Measurement Code	X	ID	2/2	Must use
		Description: Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken				
		<u>Code</u> <u>Name</u>				
		CA Case				
IT104	212	Unit Price	X	R	1/17	Must use
		Description: Price per unit of product, service, commodity, etc.				
IT106	235	Product/Service ID Qualifier	X	ID	2/2	Must use
		Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234)				
		<u>Code</u> <u>Name</u>				
		UP U.P.C. Consumer Package Code (1-5-5-1)				
IT107	234	Product/Service ID	X	AN	1/48	Must use
		Description: Identifying number for a product or service				

Syntax Rules:

1. P020304 - If either IT102, IT103 or IT104 are present, then the others are required.
2. P0607 - If either IT106 or IT107 is present, then the other is required.
3. P0809 - If either IT108 or IT109 is present, then the other is required.
4. P1011 - If either IT110 or IT111 is present, then the other is required.
5. P1213 - If either IT112 or IT113 is present, then the other is required.
6. P1415 - If either IT114 or IT115 is present, then the other is required.
7. P1617 - If either IT116 or IT117 is present, then the other is required.
8. P1819 - If either IT118 or IT119 is present, then the other is required.
9. P2021 - If either IT120 or IT121 is present, then the other is required.
10. P2223 - If either IT122 or IT123 is present, then the other is required.
11. P2425 - If either IT124 or IT125 is present, then the other is required.

Semantics:

1. IT101 is the purchase order line item identification.

Comments:

1. Element 235/234 combinations should be interpreted to include products and/or services. See the Data

Dictionary for a complete list of IDs.

- IT106 through IT125 provide for ten different product/service IDs for each item. For example: Case, Color, Drawing No., U.P.C. No., ISBN No., Model No., or SKU.

CCBCC Example:

*IT1**1*CA*10**UP*049012345678~*

Loop PID

Pos: 060	Repeat: 1000
Optional	
Loop: PID	Elements: N/A

User Option (Usage): Must use

Purpose: To describe a product or process in coded or free-form format

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
060	PID	Product/Item Description	O	1		Must use

PID Product/Item Description

Pos: 060	Max: 1
Detail - Optional	
Loop: PID	Elements: 3

User Option (Usage): Must use

Purpose: To describe a product or process in coded or free-form format

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
PID01	349	Item Description Type	M	ID	1/1	Must use
Description: Code indicating the format of a description						
Code Name						
F Free-form						
PID02	750	Product/Process Characteristic Code	O	ID	2/3	Must use
Description: Code identifying the general class of a product or process characteristic						
Code Name						
08 Product						
PID05	352	Description	X	AN	1/80	Must use
Description: A free-form description to clarify the related data elements and their content						

Syntax Rules:

1. C0403 - If PID04 is present, then PID03 is required.
2. R0405 - At least one of PID04 or PID05 is required.
3. C0703 - If PID07 is present, then PID03 is required.
4. C0804 - If PID08 is present, then PID04 is required.
5. C0905 - If PID09 is present, then PID05 is required.

Semantics:

1. Use PID03 to indicate the organization that publishes the code list being referred to.
2. PID04 should be used for industry-specific product description codes.
3. PID08 describes the physical characteristics of the product identified in PID04. A "Y" indicates that the specified attribute applies to this item; an "N" indicates it does not apply. Any other value is indeterminate.
4. PID09 is used to identify the language being used in PID05.

Comments:

1. If PID01 equals "F", then PID05 is used. If PID01 equals "S", then PID04 is used. If PID01 equals "X", then both PID04 and PID05 are used.
2. Use PID06 when necessary to refer to the product surface or layer being described in the segment.
3. PID07 specifies the individual code list of the agency specified in PID03.

CCBCC Example:

PID*F*08***20-1 CLASSIC~

TDS Total Monetary Value Summary

Pos: 010 Max: 1
 Summary - Mandatory
 Loop: N/A Elements: 1

User Option (Usage): Must use

Purpose: To specify the total invoice discounts and amounts

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
TDS01	610	Amount	M	N2	1/15	Must use

Description: Monetary amount

Semantics:

1. TDS01 is the total amount of invoice (including charges, less allowances) before terms discount (if discount is applicable).
2. TDS02 indicates the amount upon which the terms discount amount is calculated.
3. TDS03 is the amount of invoice due if paid by terms discount due date (total invoice or installment amount less cash discount).
4. TDS04 indicates the total amount of terms discount.

Comments:

1. TDS02 is required if the dollar value subject to discount is not equal to the dollar value of TDS01.

CCBCC Example:

TDS*1212~

CTT Transaction Totals

Pos: 070	Max: 1
Summary - Optional	
Loop: N/A	Elements: 2

User Option (Usage): Must use

Purpose: To transmit a hash total for a specific element in the transaction set

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
CTT01	354	Number of Line Items	M	N0	1/6	Must use

Description: Total number of line items in the transaction set

CTT02	347	Hash Total	O	R	1/10	Must use
-------	-----	------------	---	---	------	----------

Description: Sum of values of the specified data element. All values in the data element will be summed without regard to decimal points (explicit or implicit) or signs. Truncation will occur on the left most digits if the sum is greater than the maximum size of the hash total of the data element. Example: -.0018 First occurrence of value being hashed. .18 Second occurrence of value being hashed. 1.8 Third occurrence of value being hashed. 18.01 Fourth occurrence of value being hashed. ----- 1855 Hash total prior to truncation. 855 Hash total after truncation to three-digit field.

Syntax Rules:

1. P0304 - If either CTT03 or CTT04 is present, then the other is required.
2. P0506 - If either CTT05 or CTT06 is present, then the other is required.

Comments:

1. This segment is intended to provide hash totals to validate transaction completeness and correctness.

CCBCC Example:

CTT*10*25~

SE Transaction Set Trailer

Pos: 080	Max: 1
Summary - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

Purpose: To indicate the end of the transaction set and provide the count of the transmitted segments (including the beginning (ST) and ending (SE) segments)

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
SE01	96	Number of Included Segments	M	N0	1/10	Must use
		Description: Total number of segments included in a transaction set including ST and SE segments				
SE02	329	Transaction Set Control Number	M	AN	4/9	Must use
		Description: Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set				

Comments:

1. SE is the last segment of each transaction set.